











10W LED FLOOD LIGHT



AREAS OF APPLICATION

Architecture and Landscape lighting

Industrial warehouse lighting

Facade Lighting

Billboard and Advertising lighting

Security and Parking lighting

Campus and Garden lighting

Outdoor Stadium lighting

PRODUCT SPECIFICATION:

Housing: High grade Aluminium pressure Die-Cast

Lamp Efficacy: >100 lumen/Watt

System Management: Multiple LEDs are used in series - parallel cluster

Control Gear: CC-CV Control driver with efficiency >90%, current regulator for each cluster

Protection Degree: IP65/IP66

Thermal Management: Effective Heat Sinking, Ensure long life

Surge Protection: Upto 6KV

CRI: Superior color rendition index compered to HPSV, MH, Traditional lights

Special Feature: Over voltage protection, Reverse EMI protection provided, Short circuit protection, Open

circuit protection

BIS: BIS approved driver IS 15885 (Part 2/Sec13):2012, R-84000787




Technical Details:

Model No.	Rated Wattage	Nominal Voltage	Color	CRI	PF	THD	Lumen O/P
MLAC-FL10S	10W	140V-285V	CW/WW/ R/G/B	>80	>0.95	<10%	1000 lm

Dimensions:

Wattage		Length	Width	Height	
10W 135m		135mm	115mm	40mm	



Saving at a Glance:

