

60W











AREAS OF APPLICATION

Highway & Roadway lighting Campus and Garden lighting

Playground lighting

Industry lighting

Airport lighting

Outdoor Security lighting

Public Area lighting



Housing: High grade Aluminium pressure Die-Cast

Lamp Efficacy: >100 lumen/Watt

System Management: Multiple LEDs are used in series - parallel cluster

Control Gear: CC-CV Control driver with efficiency >90%, current regulator for each cluster

Protection Degree: IP65/IP66

Thermal Management: Effective Heat Sinking, Ensure long life

Optics: Quality of light design to maximize distribution & intensity

Surge Protection: Upto 10KV

CRI: Superior color rendition index compered to HPSV, MH, Traditional lights

Special Feature: Over voltage protection, Reverse EMI protection provided, Short circuit protection, Open

circuit protection

BIS: BIS approved LED street light IS 10322 (Part 5/Sec 3):2012, R-84001104







Technical Details:

Model No.	Rated Wattage	Nominal Voltage	Color	CRI	PF	THD	Lumen O/P
MLAC-SL60L	60W	140V-285V	CW/WW	>80	>0.95	<10%	6000 lm

Dimensions:

Wattage		Length	Width	Height	
	60W	385mm	185mm	60mm	





Saving at a Glance:

